

OUTDOOR PAN/TILT SCANNER

室外型左右/上下全功能迴轉台

OUTDOOR PAN/TILT SCANNER

全功能迴轉台

迴轉台

CP-504PT



SPECIFICATIONS

Angular travel	Pan: 350° ,Tilt: ±60°
Limit stop	Externally adjustable
Speed	Pan: 5°/sec
Load rating	Pan: 50Kg Tilt: 38Kg
Duty cycle	Pan: Continuous, Tilt: Intermittent
Motor output	15watts
Normal operating current	110V-0.3A
Cable requirement	6-conductor, unshielded
Operating temperature	35% to 90% (Relative humidity)
Construction	Aluminum alloy die casting
Finish	Silver gray baked enamel finish
Seals	Quad ring and gasket seals for
Input voltage	AC 110V
Operating temperature	-25°C to +60°C
Dimension	196(O)×277(H)mm
Weight	7.5kgs
Angular travel	Pan: 350° ,Tilt: ±60°
Limit stop	Externally adjustable
Speed	Pan: 5°/sec
Load rating	Pan: 50Kg Tilt: 38Kg
Duty cycle	Pan: Continuous, Tilt: Intermittent
Motor output	15watts
Normal operating current	110V-0.3A
Cable requirement	6-conductor, unshielded
Operating temperature	35% to 90% (Relative humidity)
Construction	Aluminum alloy die casting
Finish	Silver gray baked enamel finish
Seals	Quad ring and gasket seals for
Input voltage	AC 110V
Operating temperature	-25°C to +60°C
Dimension	196(O)×277(H)mm
Weight	7.5kgs

PAN/TILT SCANNER